Printing date 07/20/2023 Reviewed on 07/20/2023

### 1 Identification

· Product identifier

· Product Name: 1000 μg/mL Nickel

· Part Name: CLNI2-2Y CLNI2-2M

· Application of the substance / the mixture Certified Reference Material

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Spex CertiPrep, LLC. 203 Norcross Ave, Metuchen, NJ 08840 USA 732-549-7144

USMet-CRMSales@antylia.com

- · Information department: product safety department
- Emergency telephone number: Emergency Phone Number (24 hours) CHEMTREC (800-424-9300) Outside US: 703-527-3887

### 2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Carcinogenicity 2 H351 Suspected of causing cancer. Route of exposure: Inhalation.



Skin Irritation 2 H315 Causes skin irritation.

Eye Irritation 2A H319 Causes serious eye irritation.

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS07

- · Signal word Warning
- · Hazard-determining components of labeling:

nickel

· Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer. Route of exposure: Inhalation.

· Precautionary statements

P201 Obtain special instructions before use.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P264 Wash thoroughly after handling.

P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 If on skin: Wash with plenty of water.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.



Printing date 07/20/2023 Reviewed on 07/20/2023

Product Name: 1000 µg/mL Nickel

(Contd. of page 1)

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2 Fire = 0Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2 Fire = 0Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:			
7697-37-2 nitric acid	2.0%		
7440-02-0 nickel	0.1%		
· Chemical identification of the substance/preparation			
7732-18-5 water, distilled, conductivity or of similar purity	97.9%		

# 4 First-aid measures

- · Description of first aid measures
- $\cdot \textit{General information:} \ \textit{Immediately remove any clothing soiled by the product.}$
- $\cdot \textit{After inhalation:}$

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: Do not give anything to eat or drink Do not induce vomitting
- $\cdot \textit{Information for Doctor:}$
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

# 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

### 6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- $\cdot \textit{Environmental precautions:}$

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

 $\cdot \textit{Methods and material for containment and cleaning up:} \\$ 

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.



Printing date 07/20/2023 Reviewed on 07/20/2023

Product Name: 1000 µg/mL Nickel

(Contd. of page 2)

### · Protective Action Criteria for Chemicals

· PAC-1:				
7697-37-2 nitric acid	0.16 ppm			
7440-02-0 nickel	4.5 mg/m <sup>3</sup>			
• PAC-2:				
7697-37-2 nitric acid	24 ppm			
7440-02-0 nickel	50 mg/m <sup>3</sup>			
· PAC-3:				
7697-37-2 nitric acid	92 ppm			
7440-02-0 nickel	99 mg/m³			

# 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

### 7440-02-0 nickel

PEL	Long-term value: 1 mg/m <sup>3</sup>		
	Long-term value: 0.015 mg/m³ as Ni; See Pocket Guide App. A		
1	Long-term value: 1.5* mg/m³ elemental, *inhalable fraction, A5, BEI		
7	7 10 7 20 10 1 1 1 10 20 1		

# · Ingredients with biological limit values:

### 7440-02-0 nickel

BEI 5 μg/L

Medium: urine

Time: post-shift at end of workweek Parameter: Nickel (background)

30 μg/L Medium: urine

Time: post-shift at end of workweek

Parameter: Nickel (background)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

### Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 4)

Printing date 07/20/2023 Reviewed on 07/20/2023

Product Name: 1000 µg/mL Nickel

(Contd. of page 3)

### · Protection of hands:



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

# · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- · Eye protection:



	9	Physica	l and	c	nemi	ical	l pro	peri	ties
--	---	---------	-------	---	------	------	-------	------	------

Information on basic physical and chemical properties			
· General Information			
· Appearance:	7		
Form:	Liquid		
Color:	According to product specification		
· Odor:	Characteristic		
· Odour Threshold:	Not applicable.		
· pH-value:	Not applicable.		
· Change in condition			
Melting point/Melting range:	Undetermined.		
Boiling point/Boiling range:	100 °C (212 °F)		
· Flash point:	Not applicable.		
· Flammability (solid, gaseous):	Not applicable.		
· Decomposition temperature:	Not applicable.		
· Ignition temperature:	Product is not selfigniting.		
· Danger of explosion:	Product does not present an explosion hazard.		
· Explosion limits:			
Lower:	Not applicable.		
Upper:	Not applicable.		
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)		
· Density at 20 °C (68 °F)	$1.01797 \text{ g/cm}^3 (8.49496 \text{ lbs/gal})$		
· Relative density	Not applicable.		
· Vapor density	Not applicable.		
· Evaporation rate	Not applicable.		
· Solubility in / Miscibility with			
Water:	Fully miscible.		
· Partition coefficient (n-octanol/water): Not applicable.			
· Viscosity:			
Dynamic:	Not applicable.		
Kinematic:	Not applicable.		
· Solvent content:			
Water:	97.9 %		
VOC content:	0.00 %		
Solids content:	0.1 %		
· Other information	No further relevant information available.		

(Contd. on page 5)



Printing date 07/20/2023 Reviewed on 07/20/2023

Product Name: 1000 µg/mL Nickel

(Contd. of page 4)

### 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

7697-37-2 nitric acid

Inhalative LC50/4 h 2.65 mg/l (ATE)

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)	
7440-02-0 nickel	2B
· NTP (National Toxicology Program)	
7440-02-0 nickel	R
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	

# 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- $\cdot \textit{\textbf{Mobility in soil}} \ \textit{No further relevant information available}.$
- $\cdot \textit{Additional ecological information:}$
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agent: Water, if necessary with cleansing agents.

# 14 Transport information

- · UN-Number
- · DOT, ADR, IMDG, IATA UN3264
- · UN proper shipping name
- DOT Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid)

(Contd. on page 6)

Printing date 07/20/2023 Reviewed on 07/20/2023

Product Name: 1000 µg/mL Nickel

	(Contd. of page
· ADR · IMDG, IATA	3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID) CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID)
· Transport hazard class(es)	
$\cdot$ DOT	
CORROSVE 0	
·Class	8 Corrosive substances
· Label	8
· ADR, IMDG, IATA	
· Class	8 Corrosive substances
· Label	8
· Packing group · DOT, ADR, IMDG, IATA	III
· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Corrosive substances
The state of the s	

· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

· Hazard identification number (Kemler code):

 $\cdot ADR$ 

· EMS Number: · Segregation groups

· Stowage Category · Stowage Code

· Segregation Code

· Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

SG36 Stow "separated from" SGG18-alkalis. SG49 Stow "separated from" SGG6-cyanides

 $\cdot$  IMDG

· Limited quantities (LQ)
 · Excepted quantities (EQ)
 5L
 Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation": UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID), 8, III

8, 111

F-A,S-B

(SGG1) Acids

SW2 Clear of living quarters.

### 15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Sara

· Section 313 (Specific toxic chemical listings):

7697-37-2 nitric acid

7440-02-0 nickel

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

None of the ingredients is listed.

Proposition 65

· Chemicals known to cause cancer:

7440-02-0 nickel

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

(Contd. on page 7)

Reviewed on 07/20/2023 Printing date 07/20/2023

Product Name: 1000 µg/mL Nickel

(Contd. of page 6)

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value)

7440-02-0 nickel

A5

· NIOSH-Ca (National Institute for Occupational Safety and Health)

7440-02-0 nickel

- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS07 · Signal word Warning

· Hazard-determining components of labeling:

nickel

· Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer. Route of exposure: Inhalation.

· Precautionary statements

P201 Obtain special instructions before use.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P264 Wash thoroughly after handling.

P272 Contaminated work clothing must not be allowed out of the workplace. P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 If on skin: Wash with plenty of water.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention. P308+P313

P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: product safety department

· Contact:

Spex CertiPrep, LLC.

1-732-549-7144

· Date of preparation / last revision 07/20/2023

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

us —



# Safety Data Sheet acc. to OSHA HCS

Printing date 07/20/2023 Reviewed on 07/20/2023

Product Name: 1000 µg/mL Nickel

(Contd. of page 7)

OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
BEI: Biological Exposure Limit
Skin Irritation 2: Skin corrosion/irritation – Category 2
Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A
Sensitization - Skin 1: Skin sensitisation – Category 1
Carcinogenicity 2: Carcinogenicity – Category 2